



IWAKI  
METERING  
PUMPS

LK



Solutions for chemical handling applications

# Applicable to the many diverse needs of chemical feeding

Iwaki's systematic LK series metering pump consists of the worm gear type dual-cam driving section, which is compact yet rigid and reliable, and wet-end materials of which there are seven types for various applications.

With long and market-proven experience, Iwaki has employed state-of-the-art pump technologies in the development of an ideal type of chemical feeding pump which has advantages such as quality, performance, ease of operation and cost efficiency.

The LK series is suitable for many chemical liquid feeding processes used in a wide range of fields, including water treatment, chemicals, fabrics, paper mill, food processing, and medicine.





### Various types and materials


Nine types (IWAKI original motor) and eight general purpose motor types are available to suit each user's needs in accordance with feeding rate from small to large capacity. Also, material variation has been improved. Selection of the pump material most suitable for the applied liquid is possible with seven different types available.

### High performance and application-oriented versatile design

Discharge accuracy (stability) is within  $\pm 2\%$  FS. Reliability is considerably enhanced through efforts to improve the linearity of the stroke / discharge ratio as well as the dispersion between stroke. Three types of joints flange, hose and union joints are standardized for the connections. The optimum piping system can be selected. (Only with 0.2kW IWAKI original motor type)



## Construction



### Pump heads

Drive from the gear reduction unit is directly transmitted to the diaphragm. This type of metering pump is economical and simple with a high degree of versatility. With the employment of moulded PVC pump-head, and with the new standardisation of three types of connections using flanges, hose, or union joints (0.2kW type), not only a saving in parts cost but also improved flexibility of installation has been realized. The three main pump head materials are PVC, stainless steel, or fluororesin. The most suitable type for the application can be selected from a total of seven different materials. A wide range of chemicals, such as acid, alkaline, organic solvent, slurry, and high-temperature liquids, is covered by the series.

• Please contact us for Model PVDF.

### Drive component

The head of the LK series is the dual-cam system driving section with a highly reliable, built-in worm gear type speed reducer. The compact and rigid mechanism is a result of the design goal to achieve maximum wear resistance in continuous operation. In addition to the worm gear which is designed with a considerably large module ratio, the material is aluminium bronze, and a taper roller bearing is used at the end of the worm gear for the efficient transmission of motor power to the pump section. A fully enclosed oil bath lubrication system is employed to permit outdoor installation. The durability in continuous operation over a long period of time is also excellent.



### Motor


All of the standard models employ totally enclosed outdoor-use motors which are vertically mounted to save space. The 0.2kW type is an IWAKI original motor, which is installed in the small models of the LK series. Besides the standard 200V, other voltages are available. The LK series pumps of LK-F, LK-A, LK-B, and LK-C can be installed with general-purpose motors, including those for different voltage levels and explosion-proof specifications. Body configurations of the LK series are available in five types. They are an IWAKI original motor type frame and the general-purpose motor type frames, F, A, B and C.

### Stroke adjustment

Accurate and reliable stroke setting is possible with the micrometer type dial of the springback type stroke adjustment mechanism. An electric servo unit for automatic process control, such as flow, pressure, pH, temperature, and concentration can be arranged according to the user's needs.

#### Electric servo system Specifications

- Input signal : DC4 - 20mA (or 1 - 5V)
- Power source : AC100V 50/60Hz; other voltage types available Voltage fluctuation 10%
- Motor output : LK (0.2kW) 15W  
LK-A, B, C 40W



## Specifications

Model	Capacity L/min		Max. Pressure MPa		Stroke speed spm		Effective diaphragm dia. Ømm	Max. stroke length mm	Connection			Motor output kW	Approx net weight kg			
	Note 1		Note 2						Flange (JIS10K)	Union	Hose Ømm		PVC	SUS		
	50Hz	60Hz	PVC	SUS	50Hz	60Hz										
LK-11	0.020	0.024	1.0	1.5	48	58	22	1.5	15A (PVC)	VP16 (PVC)	4 x 9 (PVC)	0.2 (Three phase) or 0.25 (Single phase)	12	14		
21	0.050	0.060			96	116	30	2.0			12		17			
22	0.10	0.12			48	58	60	2.5			14		21			
31	0.25	0.30			96	116	48	58			16		26			
32	0.50	0.60			96	116	72	6.0	JIS16K (SUS)	12 x 18 (PVC)	-		63	80		
45	0.85	1.00			96	116	100	10					70	73		
47	1.7	2.0			96	116	25A	25A					100	100		
55	2.8	3.3			48	58	138	17.5					105	105		
57	6.0	7.2			96	116	138	17.5					120	120		
LK-A55	2.8	3.3			48	58	150	20					140	155		
A57	6.0	7.2			48	58	50A	50A					100	100		
A65	9.0	10.8			72	86	205	20					120	120		
B65	9.0	10.8	0.5	0.7	48	58	65A	65A					140	155		
B75	13.3	16.0	96	116												
C76	20	24														
C86	33	40														
C87	45	54														

Note 1: The capacity is the value when maximum discharge pressure is applied (with pure water at room temperature). The value may be larger than indicated in the table if the discharge pressure is lower.

As for the liquid conditions pumped and performance, refer to the technical information of this catalogue.

Note 2: The maximum discharge pressure of LK-A models are restricted to 0.7MPa for A55, 0.5MPa for A57 and 0.2MPa for A65 when IEC standard 0.37kW motor is adopted.

Note 3: VS type connection is different in some models from standard.

Note 4: The LK type is equipped with Iwaki original flange motor. The standard is 200V 3-phase, totally enclosed fan-cooled outdoor type.

Other motors for different voltages, explosion-proof motors, or single-phase motors are available.

LK-F, LK-A, B and C are to be installed with general purpose flange motors.

Note 5: The weight is the value when installed with a totally enclosed fan-cooled outdoor motor.



• Standard accessory : A siphon preventing valve, strainer and 4m PVC tube are furnished to hose connection type of simplex LK-11 to LK-45 VH or VC A base is furnished to all LK-A, LK-B and LK-C models.

For LK-(F) 11 to LK-(F) 57 models, the base may be supplied optionally.

• Coating color : F37-60D (JPMA) (However, the motors for LK-F/A/B/C use the maker's standard color.)

• Duplex type : LK-11 to 47 type include duplex types with a special-use integrated drive section.

## Materials



Type	VC	VH	VS4	VS	S6	S4
Application	Acids	Alkalines		Viscosity and Slurry		Solvents
Applicable type	11 to 87	11 to A57	A65 to C87	11 to C87	11 to A57	A65 to C87
1: Pump head	PVC					SUS316 SCS13
2: Valve ball	CE	HC	SUS304	HC / SUS304	HC	SUS304
3: Valve seat	Type11 to 32 Type45 to 87	FKM	EPDM	PVC	SUS316	SUS304
4: O ring	FKM					EPDM
5: Valve gasket	PTFE					PTFE
6: Diaphragm	PTFE + EPDM					
Typical chemical						
VC: Sulfuric acid, Hydrochloric acid, Sodium hypochlorite						
VH, VS4: Caustic soda, Coagulant, Calcium hydroxide (low density)						
VS: Calcium hydroxide, Highmolecular coagulant						
S6, S4: Organic solvent, Paper making chemicals						
Material symbols						
SCS13: Stainless-cast steel equivalent to SUS304						
CE: Ceramic						
FKM: Fluoro rubber						
EPDM: Ethylene propylene rubber						
HC: Hastelloy C276						

• Materials of the VS type valve balls are HC for 11 to A57 type and SUS304 for B65 to C87 type.

As for the connection, which is different in some models from standard.

• A stainless steel pump SE type for latex emulsion is available (LK-31 to 57 type).

• Material PVDF is also available. Please contact us for details.

## Pump identification

2 LK - A 65 VC H - 04 F E S

● Simplex / Duplex  
LK (Iwaki original motor type)

None: Simplex

2: Duplex (special drive section: LK-11 to 47)

LK-F/A/B/C (JEM or IEC motor type)

None: Simplex

● Series name

L series : Mechanical driven diaphragm type

● Drive section

LK (Iwaki original motor type)

None : Iwaki original motor type 0.2kW / 0.25kW

LK-F/A/B/C (JEM or IEC motor type)

F: 0.25 or 0.37 kW (for IEC), 0.4kW

A: 0.4kW

B: 0.75kW

C: 1.5kW

● Type No.

First digit : Diaphragm (pump head size)

Second digit : Speed-reducing gear ratio 1·5 : 1/30, 2·7 : 1/15, 6 : 1/20

● Motor output

LK (Iwaki original motor type)

02: 0.2kW, 03: 0.25kW (single phase)

LK-F/A/B/C (JEM or IEC motor type)

04: 0.4kW, 07: 0.75kW, 15: 1.5kW

● Material symbol

Refer to the material table

(Ex. VC, VH, VS4, VS, S6, S4)

● Joint

None : Flange

U: union (LK-11 to LK-57)

H: hose (LK-11 to LK-47)

• This table does not introduce the standard combination. Please contact us for details.  
• In case of pump without motor installation, the above item 7 and 8 are not indicated.

## Points to be observed in pump installation and piping

Iwaki metering pump LK series are reciprocating pumps employing the eccentric cam system.

Reciprocating pumps generate pulsation in the suction and discharge piping. Special consideration, (different from the ordinary centrifugal pumps), should be given to this point when planning the pump installation and piping.

### • Prevention of pipe vibration

#### Discharge side inertial resistance $P_{id} < 0.1\text{MPa}$

- $P_{id}$  : Inertial resistance on discharge side

Inertial resistance means the pulsated impact force generated by the flow just upon entering discharge stroke. It is a phenomenon particular to a reciprocating pump which is generated as a result of the sudden application of acceleration to the liquid in the discharge piping.

The condition " $P_{id} < 0.1\text{MPa}$ " is given above as an approximate standard. If  $P_{id}$  becomes 0.1MPa or higher, vibration on the pipe is generated. So measures should be taken to cope with the influence of vibration on the pump, too.

#### Measures

1. Install pulsation prevention device (air chamber).
2. Enlarge the diameter and shorten the length of the discharge piping.

### • Prevention of overfeeding

#### Pump differential pressure > Inertial resistance $P_i$

- The larger one of the suction side or the discharge side

Overfeeding means excessive flow of the liquid due to abnormal functioning of the check valve caused by pulsation of the liquid in the piping. Check carefully in case the differential pressure is low and in case the piping is too long even with the differential pressure value at 0.03MPa.

#### Measures

1. Install air chamber.
2. Install back pressure valve

### • Prevention of suction failure

#### $NPSHa > NPSHr$

$$NPSHa = Pa - Pv \pm Phs - P_{is} * MPa$$

\*Or  $P_{fs}$  : whichever is the larger.  
( $NPSH$  : Net positive suction head)

If  $NPSHa$  is insufficient, caution should be exercised because draining or cavitation occurs, which may result in poor performance or pump damage.

- $NPSHa$  : Absolute NPSH (MPa)
- $NPSHr$  : Required NPSH (value particular to the pump) (MPa)
- $P_a$  : Absolute pressure onto the tank liquid surface (MPa)
- $P_v$  : Liquid vapour pressure (MPa)
- $Phs$  : Pressure caused by the height of the suction side (MPa)  
(Flooded suction : +, Negative suction : -)
- $P_{is}$  : Inertial resistance on the suction side (MPa)
- $P_{fs}$  : Piping resistance on the suction side (MPa)

## LK series performance

Model	Viscosity mPa·s		Slurry(Calcium hydroxide) wt%		NPSHr MPa	Inertial resistance MPa/1m		Applicable chambers (0.3MPa)	
	PVC	SUS	PVC	SUS		50Hz	60Hz	PVC	SUS
LK-	11	VC: 300 VH: 500	500	—		0.07	0.001	1L	0.5L
	21			5	15	0.08	0.003		
	22			15	15	0.07	0.002		
	31		1000	15		0.08	0.003	2L	1.5L
	32			15	15	0.010	0.013		
	45			15	15	0.010	0.015		
LK-A	47	500	15		0.08	0.003	0.004	5L	5L
	55		1000	15	0.08	0.010	0.015		
	57		1000	15	0.08	0.004	0.005	10L	10L
LK-B	65	500	15		0.08	0.004	0.005		
	75		1000	15	0.08	0.003	0.005	20L	20L
LK-C	76	500	15		0.08	0.007	0.009		
	86		1000	15	0.08	0.010	0.020	20L	36L
	87		1000	15	0.013	0.020			

• Discharge capacity may reduce when sending viscous/slurry liquid. • Dosing flow fluctuation:  $\pm 2\%FS$  • Linearity deviation:  $\pm 3\%FS$

• Permissible liquid temperature PVC: 0 - 50°C, SUS: 0 - 80°C • Maximum suction lift: 1m at full stroke length • Permissible ambient temperature: 0 - 40°C • Paint color: C37-60D(JPMA)

Note 1: Inertial resistance  $P_i$  is calculated per 1m on condition that the pipeline has the same bore as the pump (by pumping clean water at full stroke length).

Determine the actual  $P_i$  by the following formula.

Inertial resistance  $P_{id}(P_{is})$ =Applicable  $P_i$  on the table×specific gravity×actual pipe length(m).....(MPa) (Pid:Discharge side Pi, Pis=Suction side Pi)

If pipe bore is different from the pump bore: Inertial resistance  $P_{id}(P_{is})$ =Applicable  $P_i$  on the table×specific gravity×actual pipe length×(Pump bore+pipe bore)<sup>2</sup>.....(MPa)

Note 2: Applicable chamber: Chamber volume is based on IWAKI's standard chambers.

## LK-VS type (Viscosity/slurry)

Model	Connection		Viscosity mPa·s	Slurry wt%	Materials		Model	Connection	Viscosity mPa·s	Slurry wt%	Materials									
	flange	hose			valve seat	valve guide														
LK-11VS	15A	*o12 x o18	5	Normal	*SUS304 (For VS)	PVC (Normal)	LK-A □ VS B □ VS C □ VS	See the standard flange connection	1000	15	*SUS304 PVC (Normal)									
		*Hose cannot be used																		

• The information marked with \* are for the VS type only.

• Suction-side piping should be flooded suction system.

## Inverter control of LK series

In case of inverter-applied control of the discharge, the control range may be different according to the types or the pressure employed.

### List of the specifications for the selection of LK series inverter control system

Model	Capacity Full stroke length L/min		Max. Pressure MPa	Control range		Stroke speed spm	Inverter frequency Hz	Motor	Description	
	PVC	PVDF		Note 1	Note 2				Note 3	
LK-F	11	0.008 - 0.032	1.0	1.5	1:4	19 - 78	20 - 80	0.2kW Standard motor (IWAKI original flange motor)	1. The frequency less than the lowest in the table cannot be used as unstable rotation of motor is expected.	
	21	0.02 - 0.08	1.0	1.5	1:4	19 - 78	20 - 80		2. Drive over the max. frequency cannot be made.	
	22	0.04 - 0.12	1.0	1.5	1:3	38 - 116	20 - 60		3. Inverter motor cannot be installed.	
	31	0.10 - 0.40	1.0	1.5	1:4	19 - 78	20 - 80			
	32	0.20 - 0.60	1.0	1.5	1:3	38 - 116	20 - 60			
	45	0.33 - 1.3	0.8	0.8	1:4	19 - 78	20 - 80			
	47	0.66 - 2.0	0.8	0.8	1:3	38 - 116	20 - 60			
	55	1.37 - 4.4	0.3	0.3	1:3.2	24 - 78	25 - 80			
	57	3.6 - 7.2	0.3	0.3	1:2	58 - 116	30 - 60			
	76	0.002 - 0.024	1.0	1.5	1:10	5 - 58	6 - 60			
LK-A	21	0.006 - 0.06	1.0	1.5	1:10	5 - 58	6 - 60	0.4kW Inverter motor (VF motor)	1. The frequency less than the lowest should not cause trouble in operation. However, such a level may affect the stability of the pump's performance.	
	22	0.012 - 0.12	1.0	1.5	1:10	11 - 116	6 - 60			
	31	0.03 - 0.30	1.0	1.5	1:10	5 - 58	6 - 60			
	32	0.06 - 0.60	1.0	1.5	1:10	11 - 116	6 - 60			
LK-B	45	0.1 - 1.0	1.0	1.0	1:10	5 - 58	6 - 60	0.75kW Inverter motor (VF motor)	1. The frequency less than the lowest cannot be used as unstable motor rotation of motor is expected.	
	47	0.2 - 1.0	—	1.5	1:5	11 - 58	12 - 60		2. Drive over the max. frequency cannot be used.	
	55	0.33 - 3.3	0.3	0.3	1:10	5 - 58	6 - 60			
LK-C	57	0.66 - 3.3	0.5	0.5	1:5	11 - 58	12 - 60	1.5kW Inverter motor (VF motor)		
	65	1.2 - 7.2	0.2	0.2	1:10	11 - 116	6 - 60			
	75	1.2 - 7.2	0.3	0.3	1:6	19 - 116	10 - 60			

Note 1: The capacity is the value when the maximum discharge pressure is applied in each type (with pure water at room temperature)

Note 2: With the LK-F type, a larger control range than 1 : 10 is available. In this case, however, the discharge accuracy and the linearity may be affected due to a stroke speed as low as 15 spm.

Note 3: The standard inverter is the Toshiba VF motor. In case of another motor used, most of the date in this list can still be used. To be sure, please contact your distributor in advance.

An inverter control with an ordinary general-purpose motor should not be employed, because it may result in trouble in the low speed range.

Note 4: When combining the following materials, the inverter frequency is "10 to 60 Hz". LK-F11VS, LK-F21VS, LK-F31VS

• This table is applied to 200V range inverter. Ask us for the inverter of other voltage.

• Two-value control by inverter and electric servo can not be done.

• It may be necessary to adjust the output torque of the motor with the inverter.

## Optional accessories

### Siphon preventing valve

Model	BVC-1P□L-□H	BVC-1P□-□H
Applicable capacity	Up to 1L/min	
Setting pressure	0.05 - 0.2MPa	0.2 - 0.8MPa
Material	PVC, FKM (EPDM)	
Connection mm (Applicable tube diameter)	Inlet Outlet	4 x 9, 12 x 18 PT3/8 and PT1/2

□: Symbol for material of O-ring ("V" for FKM, "E" for EPDM)



### Air chamber

Body	Model	Applicable capacity L	Setting pressure MPa	Connection Nominal size JIS10K flange	Weight kg
PVC	A-1V□	1.0	0.5	Common for 15A - 25A	2
	A-2V□	2.0		40A	2.5
	A-5V□	5.0		50A	4.5
	N40A-10V(2)-F *	10		65A	16
	N50A-20V(2)-F *	20		10, 15, 20A	26
	N65A-30V(2)-F *	30		15, 20, 25A	49
SUS316	A-05S6-( )	0.5	0.9	25, 40A	3
	A-15S6-( )	1.5		40, 50A	5
	A-5S6-( )	5.0		50, 65A	12
	A-10S6-( )	10		65A	15
	A-20S6-( )	20			29
	A-36S6-( )	36			55

\*: Material for O-ring 10V / 20V / 30V for CR, 10V2 / 20V2 / 30V2 for FKM

□: Symbol for material of O-ring ("V" for FKM, "E" for EPDM)


( ): Symbol for connection (10, 15, 20, 25, 40, 50 or 65)

• The weight is the value of the product only. (The weight of liquid applied is not included.)

• Rigid PVC chamber may deteriorate with ultraviolet ray or the applied chemical liquid over a long period of time. The chamber should be replaced every three years to guarantee safety.



### Relief valve and back pressure valve



#### List of relief valve

Body	Model	Max. capacity L/min	Setting pressure MPa	Connection Nominal size JIS10K flange	Weight kg
PVC	RV-1P□-4H	1.0	0.3 - 0.8	ø4 x ø9 PVC Hose	0.2
	RV-1P□-12H	1.0	0.3 - 0.8	ø12 x ø18 PVC Hose	0.2
	RV-1P□-15	1.0	0.3 - 0.8	15A	0.5
	RV-1P□-20	1.0	0.3 - 0.8	20A	0.5
	RV-1P□-B-15	1.0	0.8 - 1.0	15A	0.5
	RV-3P-15	3.0	0.3 - 1.0	15A	0.6
	RV-3P-20	3.0	0.3 - 1.0	20A	0.6
	RV-3P-25	3.0	0.3 - 1.0	25A	0.9
	RV-3P□-12H	3.0	0.3 - 1.0	ø12 x ø18 PVC Hose	0.4
	RV-7V-20	7.5	0.3 - 0.8	20A	3.5
	RV-7V-25	7.5	0.3 - 0.8	25A	3.5
	RV-7VB-20	7.5	0.8 - 1.0	20A	3.5
	RV-7VB-25	7.5	0.8 - 1.0	25A	3.5
	RV-25V-25	25	0.3 - 0.8	25A	4
SUS	RV-25V-40	25	0.3 - 0.8	40A	4
	RV-25V-50	25	0.3 - 0.8	50A	4.5
	N50RV-5V-F	50	0.15 - 0.5	50A	20
	N50RV-5V2-F	50	0.15 - 0.5	50A	20
	N65-50RV-5V-F	70	0.15 - 0.5	65A	20
	N65-50RV-5V2-F	70	0.15 - 0.5	65A	20
	RV-25G-15	2.0	0.3 - 0.8	JIS10 - 16K 15A	3.5
	RV-25G-15	2.0	0.8 - 1.5	JIS10 - 16K 15A	3.5
	RV-7S6-25	7.5	0.3 - 0.8	JIS10 - 16K 25A	6
	RV-7S6-25	7.5	0.8 - 1.5	JIS10 - 16K 25A	6
	RV-25S6-25	25	0.3 - 0.8	25A	7.0
	RV-25S6B-25	25	0.8 - 1.0	25A	7.0
	RV-25S6-40	25	0.3 - 0.8	40A	7.5
	RV-25S6-50	25	0.3 - 0.8	50A	8.7
	RV-25S6B-40	25	0.8 - 1.0	40A	7.5
	N50RV-5S6-F	80	0.15 - 0.5	50A	29
	N65RV-5S6-F	120	0.15 - 0.5	65A	42

□: Symbol for material of O-ring ("V" for FKM, "E" for EPDM)

O-ring material of N type is "5V2" for FKM.

• Material for diaphragm is PTFE except RV-1P and N type.

Material of diaphragm is same as O-ring material at RV-1P and N type.

#### List of back pressure valve

Body	Model	Max. capacity L/min	Setting pressure MPa	Connection Nominal size JIS10K flange	Weight kg
PVC	BV-1P□-4H	0.005 - 1.0	0.2 - 0.8	ø4 x ø9 PVC Hose	0.2
	BV-1P□-12H	0.005 - 1.0	0.2 - 0.8	ø12 x ø18 PVC Hose	0.2
	BV-1P□-15	0.005 - 1.0	0.2 - 0.8	15A	0.5
	BV-1P□-20	0.005 - 1.0	0.2 - 0.8	20A	0.5
	BV-1P□-4H	0.005 - 1.0	0.05 - 0.2	ø4 x ø9 PVC Hose	0.2
	BV-1P□-L-12H	0.005 - 1.0	0.05 - 0.2	ø12 x ø18 PVC Hose	0.2
	BV-1P□-L-15	0.005 - 1.0	0.05 - 0.2	15A	0.5
	BV-1P□-L-20	0.005 - 1.0	0.05 - 0.2	20A	0.5
	BV-3P□-12H	0.03 - 3.0	0.1 - 0.8	ø12 x ø18 PVC Hose	0.4
	BV-3N□-12H	0.005 - 3.0	0.1 - 0.3	ø12 x ø18 PVC Hose	0.4
	BV-3N□-15	0.005 - 3.0	0.1 - 0.3	15A	0.6
	BV-3N□-20	0.005 - 3.0	0.1 - 0.3	20A	0.6
	BV-3N□-25	0.005 - 3.0	0.1 - 0.3	25A	0.9
SUS	BV-7V-20	0.2 - 7.5	0.05 - 0.8	20A	3.5
	BV-7V-25	0.2 - 7.5	0.05 - 0.8	25A	3.5
	BV-25V-25	2 - 25	0.1 - 0.8	25A	4
	BV-25V-40	2 - 25	0.1 - 0.8	40A	4
	BV-25V-50	2 - 25	0.1 - 0.8	50A	4.5
	N50BV-5V-F	2.5 - 50	0.15 - 0.5	50A	18
	N50BV-5V2-F	2.5 - 50	0.15 - 0.5	50A	18
	N65-50BV-5V-F	5 - 70	0.15 - 0.5	65A	20
	N65-50BV-5V2-F	5 - 70	0.15 - 0.5	65A	20
	BV-25G-15	0.02 - 2.0	0.05 - 0.8	JIS10 - 16K 15A	3.5
	BV-7S6-25	0.2 - 7.5	0.05 - 0.8	JIS10 - 16K 25A	6.0
	BV-25S6-25	2 - 25	0.1 - 0.8	25A	7.0
	BV-25S6-40	2 - 25	0.1 - 0.8	40A	7.5
	BV-25S6-50	2 - 25	0.1 - 0.8	50A	8.5
	N50BV-5S6-F	2.5 - 80	0.15 - 0.5	50A	29
	N65BV-5S6-F	5 - 120	0.15 - 0.5	65A	42

□: Symbol for material of O-ring ("V" for FKM, "E" for EPDM)

O-ring material or N type is "5V" for CR, or "5V2" for FKM.

• Material for diaphragm is PTFE except BV-1P and N type.


Material of diaphragm is same as O-ring material at BV-1P and N type.

• The back pressure valve can not curb the residual flow completely when the pump stops.

Use the solenoid valve in order to shut out the residual flow.

**Dimensions (in mm)**


Dimensions may be changed without prior notice for the purpose of product improvement.  
Be sure to carry out installation work with the most recent and detailed drawings, which are available upon request.

**LK-11 to LK-57 (Original motor type)**

Model	Hose type PVC					Union type PVC					Flange type PVC					Flange type SUS					
	L	a	b	c	m	L	a	b	c	m	L	a	b	c	d	m	L	a	b	c	m
<b>LK-1</b>	274	146	23	95		274	244	72	95	16	275	264	86	95	89	15	272	141	20	92	15
<b>2</b>	274	164	32	95		274	262	81	95	16	275	282	95	95	89	15	272	151	25	92	15
<b>3</b>	277	224	62	97		277	318	109	97	16	277	342	125	97	89	15	277	184	42	97	15
<b>4</b>	281	249	75	99	1	281	342	120	99	16	281	361	135	99	89	15	283	261	80	101	15
<b>5</b>	-	-	-	-		298	314	107	114	25	298	338	125	114	97	25	295	320	111	111	25
<b>47VS</b>	-	-	-	-		281	272	86	99	25	281	313	106	99	97	25	-	-	-	-	-


Note 1: Connection size LK-1 and LK-2 ø4mm x ø9mm, LK-3, LK-4 and LK-1 to LK-45 VS type ø12mm x ø18mm.

For information of TC type, please contact IWAKI or nearest distributor.

**LK-A55 to LK-C87 (General purpose motor type)**

Model	PVC					SUS					Note 2				
	L	a	b	c	m	L	a	b	c	m	H	d	e	f	g
<b>LK-A5</b>	476	325	-29	119	119	473	320	-32	108	547	180	240	260	300	25
<b>A6</b>	532	599	108	154	533	431	24	164	547	180	240	260	300	40	
<b>B6</b>	595	599	90	164	605	431	6	174	594	240	300	310	350	40	
<b>B7</b>	599	600	90	167	610	465	23	178	594	240	300	310	350	50	
<b>C7</b>	599	600	90	167	610	465	23	178	601	240	300	310	350	50	
<b>C8</b>	605	647	114	173	609	633	107	177	601	240	300	310	350	65	

Note 2: These dimensions are common between PVC pump head and SUS pump head.

**LK-F1 to F5 (General purpose motor type)**


Model	Hose type PVC					Union type PVC					Flange type PVC					Flange type SUS						
	L	a	b	c	m	L	a	b	c	m	L	a	b	c	d	m	L	a	b	c	d	m
<b>LK-F1</b>	274	146	177	87		274	244	128	87	16	363	272	114	87	89	15	332	156	180	85	60	15
<b>2</b>	274	164	168	87		274	262	119	87	16	363	290	105	87	89	15	332	166	175	85	60	15
<b>3</b>	277	224	138	89	1	277	318	91	89	16	366	350	75	89	89	15	337	201	158	90	60	15
<b>4</b>	281	249	128	92		281	342	79	92	16	370	369	65	92	89	15	343	270	120	94	60	15
<b>5</b>	-	-	-	-		298	314	93	107	25	395	350	75	107	97	25	399	368	90	104	25	
<b>47VS</b>	-	-	-	-		281	272	114	92	25	378	313	94	92	97	25	-	-	-	-	-	-

Note 1: Connection size LK-1 and LK-2 ø4mm x ø9mm, LK-3, LK-4 and LK-1 to LK-45 VS type ø12mm x ø18mm.

For information of TC type, please contact IWAKI or nearest distributor.

**Pump controller****MFC****Multifunction pump controller  
for LK-F series metering pumps**

- Capable of analogue input (4~20mA) and pulse input (Dividing/Multiply) operation
- Operating functions of the pump can be monitored via external output signal.
- Easy key touch operation and a large LCD display give good control legibility.
- Display preference of flow rate (L/min) or stroke rate (SPM) is user-selectable.
- Combination of stroke length adjustment
- with stroke rate enables flow volume control over a wide range of 1:480.

**Control system**

IWAKI CO., LTD. 6-6 Kanda-Sudacho 2-chome Chiyoda-ku Tokyo 101-8558 Japan TEL : (81)3 3254 2935 FAX : 3 3252 8892

IWAKI has global net work.

[www.iwakipumps.jp](http://www.iwakipumps.jp)

European office : IWAKI Europe GmbH  
Germany : IWAKI Europe GmbH  
Holland : IWAKI Europe GmbH (Netherlands Branch)  
Italy : IWAKI Europe GmbH (Italy Branch)  
Spain : IWAKI Europe GmbH (Spain Branch)  
Belgium : IWAKI Belgium N.V.  
Denmark : IWAKI Nordic A/S  
Finland : IWAKI Suomi Oy  
France : IWAKI France S.A.  
Norway : IWAKI Norge AS  
Sweden : IWAKI Sverige AB  
U.K. : IWAKI Pumps (UK) Ltd.

TEL: (49)2154 9254 0 FAX: 2154 9254 48  
TEL: (49)2154 9254 50 FAX: 2154 9254 55  
TEL: (31)74 2420011 FAX: (49)2154 9254 48  
TEL: (39)0444 371115 FAX: 0444 335350  
TEL: (34)93 37 70 198 FAX: 93 47 40 991  
TEL: (45)48 24 2345 FAX: 48 24 2346  
TEL: (33)1 69 63 33 70 FAX: 1 64 49 92 73  
TEL: (47)23 38 49 00 FAX: 23 38 49 01  
TEL: (46)8 511 72900 FAX: 8 511 72922  
TEL: (44)1743 231363 FAX: 1743 366507  
(Country codes)

U.S.A. : IWAKI America Inc.  
Argentina : IWAKI America Inc. (Argentina Branch)  
Brasil : IWAKI Do Brasil Comercio De Bombas Hidraulicas LTDA.  
Singapore : IWAKI Singapore Pte Ltd.  
Indonesia : IWAKI Singapore (Indonesia Office)  
Malaysia : IWAKI Sdn. Bhd.  
Australia : IWAKI Pumps Australia Pty Ltd.  
Hong Kong : IWAKI Pumps Co., Ltd.  
China : GFZT IWAKI Engineering & Trading Co., Ltd.  
Korea : IWAKI Korea Co., Ltd.  
Taiwan : IWAKI Pumps Taiwan Co., Ltd.  
Thailand : IWAKI (Thailand) Co., Ltd.

TEL: (1)508 429 1440 FAX: 508 429 1386  
TEL: (541)1 4745 4116 FAX: 19 3244 5900  
TEL: (65)6316 2028 FAX: 6316 3221  
TEL: (62)21 6906606 FAX: 21 6906612  
TEL: (60)3 7803 8807 FAX: 3 7803 4800  
TEL: (61)2 9899 2411 FAX: 2 9899 2421  
TEL: (85)2607 1168 FAX: 2607 1000  
TEL: (86)20 84350603 FAX: 20 84359181  
TEL: (86)21 6272 7502 FAX: 21 6272 6929  
TEL: (82)2 2630 4800 FAX: 2 2630 4801  
TEL: (886)2 8227 6900 FAX: 2 8227 6818  
TEL: (66)2 322 2471 FAX: 2 322 2477